

# Instructions for wear checks of play equipment

The equipment must be checked for correct operation and safety, especially the points listed below:

Proof of maintenance

Playground.....

Date of installation .....


Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on

- the location
- the usage
- the frequency of use
- possible vandalism

For more details see also "General instructions for maintenance of playgrounds".

**Totter Trail Type 01**  
**Order No. 4.03010**



## Structural stability

1. Uncover the foundations once a year in order to check the structural stability as follows:
  - wood for rot
  - steel for corrosion
  - anchoring to the ground for stability
  - condition of concrete foundations
2. Check that all bolts and screws as well as all wood joints are tight, retighten if necessary.

## Wooden parts

3. Check for rot and, if necessary, smooth out splinters and round off sharp edges and cracks.
4. Check steps for wear and tear: at least 2/3 of the material should be left, replace if necessary.
5. Recommendation: apply paraffin wax to the end grain areas once a year, especially near the ground; please refer to Order No. 0.90100, 1 litre.

## Ropes and rope connections

6. Check that ropes are securely connected, retighten if necessary.
7. Check ropes for wear and tear, if the steel reinforcement is damaged it is imperative they be replaced.

Note: Clean the inside of the crawl barrel, if necessary.








Special notes, e.g. for repairs

Repair not carried out, it is still possible to play on equipment

Repair not carried out, equipment is taken out of action

All work carried out, everything is in order

Maintenance carried out by:

..... Date .....