

Instructions for wear checks of play equipment

The equipment must be checked for correct operation and safety, especially the points listed below:

Proof of maintenance

Playground

Date of installation


Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on

- location
- kind of use
- frequency of use
- possible vandalism

For more details see also "General instructions for maintenance of playgrounds".

See-saw with shock absorbers
Order No. 6.11000/6.11010



Wooden parts

1. Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks.

See-saw mechanism

2. Check that all bolts and screws are tight and retighten if necessary.
3. Check brass bush for wear and tear, replace if necessary.

Shock absorbers

4. Check spring effect of up and down movement; the beam must stop smoothly.

Handles

5. Check for stability.

Structural stability

6. In order to check the stability of the foundation or the steel feet for corrosion, uncover the foundation once a year.

Special notes, e.g. for repairs

Repair not carried out, it is still possible to play on equipment

Repair not carried out, equipment is taken out of action


All work carried out, everything is in order

Maintenance carried out by:

For spare parts refer to back of page.

..... Date


Spare Parts
See-saw with
shock absorbers
Order No. 6.11000/6.11010



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts**.

Order No. Spare part


0.92240 see-saw mechanism
with shock absorbers




0.92245 brass bush



0.92246 rubber buffer



0.92260 upper part for see-saw mechanism



0.92250 handle for sea-saw

