

Inspection and maintenance notes

The combination must be checked for correct operation and safety, especially the points listed below:

Proof of maintenance

Playground.....

Date of installation


Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on:

- location
- usage
- frequency of use
- possible vandalism

For more details see also "General instructions for maintenance of playgrounds".

Rope Course Type 01
Order No. 6.49010



Concrete

1. Check for vandalism (chipped edges), and if necessary deburr sharp edges with an angle grinder or mend them with fast drying concrete or epoxy resin.

Ropes and nets

2. Check the connections of rope and net elements for damage and ensure they are tight, retighten if necessary.
3. Check plastic sleeves of rope and net elements for wear and tear; replace any elements whose inner steel strands are damaged.

Structural stability

4. Have trained personnel check the condition of the concrete columns **twice** a year. Dig around the columns down to the foundation before carrying out this step.

Attention!
Strictly adhere to the maintenance intervals!

Special notes, e.g. for repairs

Repair not carried out, it is still possible to play on equipment

Repair not carried out, equipment is taken out of action

All work carried out, everything is in order

Maintenance carried out by:
..... Date

En-EN 07.05.2020

COPYRIGHT © RICHTER SPIELGERÄTE GMBH