# Play value

We developed a new version with a cross beam made of steel to give the Toddler's Twin Swing a special design. The sophisticated corner connection ensures extra stability for the entire construction. No playground is complete without a swing. It is important that children are offered the right equipment to promote development. Swinging to-and-fro is a basic movement and is not just fun for children. Swinging releases stress, has a comforting effect and is very enjoyable, especially done together next to one another.





Order No. 6.12020 Toddler's Swing - special



Order No. 6.12720 Toddler's Twin Swing – special

# **Fundamental characteristics**

- Aesthetically appealing design
- Incentive for playing: repeating familiar activities
- Movement: swinging, jumping off

# **Recommended for**

- Children under 3 years
- Kindergarten children
- Supervised play areas, such as kindergartens, schools, after-school programmes or similar
- Public play areas without supervision, such as playgrounds, parks or similar

Toddler's Swing – special Toddler's Twin Swing – special





6.12020

# Order No. 6.12020 Order No. 6.12720 Toddler's Swing - special Toddler's Twin Swing - special 340 340 680 680 340 310 175 370 225 440 255 Safety distance **Device dimensions** Functional distance Scale 1:100

Safety check according to DIN EN 1176

### Components

# Order No. 6.12020 Toddler's Swing - special

- Swing with steel feet and cross beam made of steel
- Toddler belt seat with chains

- Swing with steel feet and cross beam made of steel
- 2 Toddler belt seats with chains

# Order No. 6.12720 Toddler's Twin Swing – special

# Attention:

Exact measurements may vary; for all installation dimensions refer to current installation instructions. Technical changes reserved.

corresponding to a fall height of ≤ 1.00 m

(please refer to price list for more

Installation information

Surfacing requirements

detailed information)

Order No. 6.12020

Order No. 6.12720

2 items 60 x 60 x 60 cm

Excavation depth 80 cm

4 items 60 x 70 x 40 cm

Excavation depth 60 cm

Foundations



Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced

Equipment made of non-impregnated



**Swing joint** 

mountain larch **Peeled white** 

Drop-forged, hot-dip galvanised swing joint with sintered bush and integrated



# **Profiled washer**

**Technical information** 

Profiled washer for covering protruding screw heads according to standard, improved pressure distribution and protection against water. Impedes loosening the bolt



#### Sintered bush

For all reciprocating movements we use sintered plain bearings which are self-lubricating in use and can easily be exchanged if necessary



#### **Ground anchor**

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



# Cross beam made of steel

Swing cross beam made of hot-dip galvanized steel.



Optimized swing geometry with rigid corner connections, thus allowing for smaller foundations and easier foundation covering

#### **Chains**

Chains made of hot-dip galvanized steel (1.4301 / 1.4571 at extra charge) welded before galvanising, short-linked, without eyelets on the connecting parts, easy to exchange and shorten



Flexible swing seat made of steel reinforced rubber

# Order No. 6.12720

As above, but in addition with

### Interlocking

Interlocking connection, with milled metal rings or serrated disc dowels, to reinforce the bolt connection under high loads transverse to the grain direction of the wood



For more detailed explanation of the quality characteristics see price list.

#### **Dimensions**

(small deviations possible)

### Order No. 6.12020 Toddler's Swing - special

Height	1.95 m
Vertical clearance	1.70 m
Width	2.25 m
Weight	130 kg

#### Order No. 6.12720 Toddler's Twin Swing - special

3	
<b>Height</b>	1.90 m
Vertical clearance	1.70 m
Width	3.70 m
Weight	180 kg



6.12020