Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:		Proof of maintenance	
Playground	1. Che splii 2. Che retig 3. Rec wax Sp 4. Clea (ww. 5. Che adju 6. Rep Str	coden parts cok for rot and, if necessary, smooth out inters and round off sharp edges of cracks. cok that all bolts and screws are tight and ighten if necessary. commendation: apply wood preservative is (www.complex-farben.eu) once a year. chere suspension an with stainless steel spray in which in the spheres form an exact line, resust if necessary (see detailed diagram*). colace spheres if necessary. cuctural stability rder to check that the equipment is		
Impulse Spheres Order No. 10.11000 angled rail stop nut M6 top detailed diagram stop nut M6 bottom * Note on step 5: The nuts at the bottom of the angled rails must not be tightened to the end of their threads (approx. 1 mm gap, see detailed diagram).				Special notes, e.g. for repairs
7	Repair n equipme	ot carried out, possible to play on equipment ot carried out, ent is taken out of action carried out, ng is in order		
For spare parts refer to back of page.	Maintenance carried out by: Date			

Spare Parts Impulse Spheres Order No. 10.11000



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts**.


Order No. Spare part

Order No. Spare part

10.99903 sphere with cable



10.99904 sphere suspension gear with 9 spheres



10.99934 set of ropes with eyebolts and nuts w/o illustr. (for 9 spheres)