## Instructions for wear checks of play equipment

## Playground.....

- the location
- the usage
- the frequency of use
- possible vandalism

## For more details see also "General instructions for maintenance of playgrounds".

## Swallow's Cradle Nest special Order No. 6.14720/K6.14720

detailed diag	ıram	I
9 Note	-	l
The first chain link r be firmly locked.	nust	ļ

Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance	
Playground	Structural stability		
Date of installation	<ol> <li>Uncover the foundations once a year in order to check the structural stability as follows:</li> <li>steel for corrosion</li> </ol>		
Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.	<ul> <li>anchoring to the ground for stability</li> <li>condition of concrete foundations</li> </ul>		
Intervals for maintenance work and checks generally depend on	<ol> <li>Check that all screws and bolts as well as all wood joints are tight, retighten if necessary. Shorten any protruding threads and re- galvanise with galvanizing spray.</li> </ol>		
- the location - the usage	Wooden parts		
<ul><li>the frequency of use</li><li>possible vandalism</li></ul>	3. Check for rot and, if necessary, smooth out splinters and round off sharp edges and cracks.		
For more details see also "General instructions for maintenance of playgrounds".	<ol> <li>Recommendation: apply paraffin wax to the end grain areas once a year, especially near the ground; please refer to order No. 0.90100, 1 litre.</li> </ol>		
Swallow's Cradle Nest special	Metal/fittings		
Order No. 6.14720/K6.14720	5. Check drop-forged joint yoke – the opening must be parallel to the metal cross beam.		
	<ol><li>Check that joints can move smoothly in both directions.</li></ol>		
	<ol> <li>Also make sure that the swivels move smoothly, apply small amount ofgrease if required.</li> </ol>		
4	<ol> <li>Check welding seams on the metal cross bar for cracks.</li> </ol>		
	9. Check chain and connection to chain; the first chain link must be locked; check wear on contact surfaces between first and second chain link, <b>see detailed diagram.</b>	Special notes, e.g. for repairs	
	Swallow nest	tes, e.ç	
	10. Check for damage and for wear and tear, replace if necessary.	Special no	
detailed diagram	Repair not carried out, it is still possible to play on equipment		
9 Note	Repair not carried out, equipment is taken out of action		
The first chain link must be firmly locked.	All work carried out, everything is in order		
	Maintenance carried out by:		
For spare parts refer to back of page.	Date		

Spare parts Swallow's Cradle Nest special Order No. 6.14720



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts**.

Order No.	Spare part	Order No.	Spare part
0.86200	swallow's nest for replacement without joints	0.20012 Ø	stainless steel machine screws reinforced, with locking nut
0,86291	owellow's post for replacement	0.88193	square block steel, reinforced with 2 brass bushes
	swallow's nest for replacement without joints and chains	0.88140	brass bush
0.93133	swing joint, complete		
	udes only the spare parts ordered ently. Other spare parts on		