Instructions for wear checks of play equipment

The equipment must be checked for correct operation and safety, especially the the points listed below:

Proof of maintenance

Playground.....

Date of installation


Equipment-specific inspections must be carried out at least twice a year.

Intervals for maintenance work and checks generally depend on

- the location
- the usage
- the frequency of use
- possible vandalism

For more details see also our general instructions for maintenance of climbing forests and playgrounds!

Horizontal Triangular Net Order No. L6.51640/L6.51642



Ropes and net

- 1. Ensure that rope and net elements are securely connected and check connection points for damage; retighten screws/bolts if necessary.
- Check plastic sleeves of the rope and net elements for wear and tear; replace any elements whose inner steel strands are damaged.



Attention Strictly adhere to the maintenance intervals!

Wooden parts

- Check for rot and, if necessary, smooth out splinters and round off sharp edges cracks
- 4. Check that all bolts and screws are tight and retighten if necessary
- Recommendation: apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre

Structural stability

6. In order to check the steel feet for corrosion, uncover the foundation once a year

Metal/fittings

- Developed sharp edges file stub
- 8. Make sure that the joints and swivels move smoothly, apply grease if required

Repair not carried out, it is still possible to play on equipment

Repair not carried out, equipment is taken out of action

All work carried out, everything is in order

Date	
. Date	

Special notes, e.g. for repairs