Inis copy may be copied for maintenance of Richter play equipment.		
Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
Playground	Bubble	
Date of installation	Make sure that the swivels move smoothly, apply grease if required.	
Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.	Check chain and connection to chain, the first chain link must be locked; check wear on contact surfaces between first and second chain link.	
Intervals for maintenance work and checks generally depend on	Check deflection limitation for function.	
- location	Wooden parts	
usagefrequency of usepossible vandalism	Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks.	
For more details see also our general instructions for maintenance of playgrounds!	Check that all bolts and screws are tight and retighten if necessary.	
	Ropes	
Bubble House 01	Check for wear and tear. Replace if steel reinforcement is damaged.	
consisting of 3 Pipe bends Order No. 8.00100	7. Check that connection points are tight and retighten if necessary.	
	Frame	
	8. Check for vandalism.	
	Check the screw and bolt connections to the base equipment for firmness, thighten if necessary.	<u>«</u>
	Structural stability	repai
Bubble House 02 consisting of 2 Pipe bends Order No. 8.00200	In order to check steel feet for corrosion, uncover the foundations once a year.	Special notes, e.g. for repairs
		Specir
	Repair not carried out, it is still possible to play on equipment	
	Repair not carried out, equipment is taken out of action	
	All work carried out, everything is in order	
	Maintenance carried out by:	
	Date	