Inis copy may be copied for maintenance of Richter pla		Page 1	
Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance	
Playground	Wooden parts		
Date of installation	Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks.		
Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.	Check that all bolts and screws are tight and retighten if necessary.		
Intervals for maintenance work and checks generally depend on	Check the ash wood rungs of the ladders for wear and tear, the remaining diameter must be at least 30 mm.		
locationusagefrequency of usepossible vandalism	4. Recommendation : apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre.		
- possible varidalism	Structural stability		
For more details see also our general instructions for maintenance of playgrounds!	5. In order to check for rot at wooden parts and steel feet for corrosion, uncover the foundations once a year.		
Pentagonal Tower with ladder without roof Order No. L3.20700 height 1.50 m Order No. L3.20850 height 2.00 m		Special notes, e.g. for repairs	
	Repair not carried out, it is still possible to play on equipment		
5	Repair not carried out, equipment is taken out of action		
	All work carried out, everything is in order		
For spare parts refer to back of page.	Maintenance carried out by:		

Spare parts Pentagonal Tower Order No. L3.20700/L3.20850		Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to only use original parts .
Order No.	Spare parts	
0.92620	Ladder	
0.98310	Ladder Rung incl. screws	